

Sapa Window 1086 in composite wall inward opening/ fixed

Instructions.

Isolated window in aluminum Sapa Windows 1086 in composite wall.

Profile depth 86 mm.

Wall thickness 100mm/ 120mm/ 150mm/ 160mm/ 175mm/ 200mm/ 230mm/ 240mm.

Fixed/ inward opening side hung/ inward opening bottom hung/ inward opening top hung/
inward opening side bottom hung.

Surface treatment anodizing nature/ HX 5/ HX 10/ HX 20/ HX 30/ HX 40/ HX 50.

Surface treatment powder coating 60 μm , pretreatment acc. to Sapa std. Color NCS S/ RAL.

Double glass/ Triple glass/ toughened/ laminated/ sunscreen.

Max. U-value for the whole construction.

Sound insulation: Rw/ Rw+Ctr.

Handle/ lockable handle/ removable handle acc. to Sapa std.

Restrictor acc. to Sapa std.

Friction stay acc. to Sapa std.

Window stop acc. to Sapa std.

Installation and connections acc. to Sapa instructions.

Select one alternative.

Select one alternative.

Select one type.

Select color.

Select alternative. Glass thickness 20-64mm.

Select U-value.

Select type and dB.

Select one alternative.

For top hung windows.

For side or bottom hung windows.

For side or bottom hung windows.